



111305 / 08 / 13

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Clear glass diffuser, UV stabilized with a better light output.

Reflector - Aluminium tiles pattern reflector, UV stabilized.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).


Objective

This luminaire is a good choice in matter of design and power. This high efficiency of the LED source ensures excellent performances and low consumptions. Energy and economy savings are a little advantage compared to the design of this item. Completely dustproof. Protected against splash of water.

Obiettivo

Questo apparecchio è una buona scelta in termini di design e potenza. Questa elevata efficienza della sorgente LED garantisce prestazioni eccellenti e bassi consumi. Risparmio energetico ed economico sono un piccolo vantaggio rispetto al design di questo prodotto. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.



	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	111305	5W	COB	44	95 lm/W	Ø70 x H65mm Ø65mm
	111308	8W	COB	44	95 lm/W	Ø70 x H65mm Ø65mm
	111313	13W	COB	44	95 lm/W	Ø110 x H65mm Ø65mm



Color Options

(W)

Beam Angle



2700K
3000K
4000K
5000K
6000K

TRIAC
DALI
1-10
Dimming
Phase
Dimming

