



111508 / 13

### Description

**Housing** - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

**Diffuser** - Clear glass diffuser, UV stabilized with a better light output.

**Reflector** - Aluminium reflector, UV stabilized.

**Mounting** - LED Recessed mounted.

**Standards** - Manufactured in accordance with IEC 62722.

**LED** - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

### Objective


This luminaire is a good choice in matter of design and power. This high efficiency of the LED source ensures excellent performances and low consumptions. Energy and economy savings are a little advantage compared to the design of this item. Completely dustproof. Protected against splash of water.

### Obiettivo

Questo apparecchio è una buona scelta in termini di design e potenza. Questa elevata efficienza della sorgente LED garantisce prestazioni eccellenti e bassi consumi. Risparmio energetico ed economico sono un piccolo vantaggio rispetto al design di questo prodotto. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.

| CODE | POWER | CHIP | IP | LUMENS | DIMENSION |
|------|-------|------|----|--------|-----------|
|------|-------|------|----|--------|-----------|



|        |     |     |    |         |                     |
|--------|-----|-----|----|---------|---------------------|
| 111508 | 8W  | COB | 54 | 95 lm/W | Ø79 x H65mm  Ø65mm  |
| 111513 | 13W | COB | 54 | 95 lm/W | Ø110 x H85mm  Ø95mm |



Beam Angle

Color Options

(W)



2700K  
3000K  
4000K  
5000K  
6000K

DALI  
1-10 Dimming  
Phase Dimming

