



112106 / 10 / 15

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass / PMMA / diffuser, UV stabilized with a better light output.

Reflector - Aluminium reflector, UV stabilized.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722..

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

This spotlight series are popular for its different installation ways; fixed or adjustable, trim or trimless for direct lighting or wall washing. with the feature of dark light reflector this provides a high level of comfortable visual and optimum light output ratio. Different optical lens with beam angle. Efficient & Deliver high quality Warm & pleasant light. Completely dustproof. Protected against splash of water.

Obbiettivo

Questa serie di faretti è famosa per le sue diverse modalità di installazione; fisso o regolabile, trim o trimless per illuminazione diretta o lavaggio a parete. con la caratteristica del riflettore dark light, questo offre un alto livello di comfort visivo e un rapporto di emissione luminosa ottimale. Diverse lenti ottiche con angolo del fascio. Efficiente e fornisce luce calda e piacevole di alta qualità. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	112106	6W	COB	54	95 lm/W	Ø68.5 x 68mm
	112110	10W	COB	54	95 lm/W	Ø68.5 x 68mm
	112115	15W	COB	54	95 lm/W	Ø68.5 x 107mm

