



112407 / 13 / 20

Description

Housing - Die cast aluminium with powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Polycarbonate clear diffuser, UV stabilized with a better light output.

Reflector - PMMA reflector, UV stabilized.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective



High efficiency LED downlight. This fitting gives great functionality and efficiency. The design is consistent. The light provided from this luminaire is uniform and there is no glare effect. Expect LED energy saving consumption and durability. Completely dustproof. Protected against splash of water.

Obiettivo

Downlight LED ad alta efficienza. Questo raccordo offre grande funzionalità ed efficienza. Il design è coerente. La luce fornita da questo apparecchio è uniforme e non vi è alcun effetto di abbagliamento. Aspettatevi consumi e durata a risparmio energetico a LED. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	112407	7W	SMD	54	85 lm/W	Ø70 x H70mm ☞ Ø65mm
	112413	13W	SMD	54	85 lm/W	Ø85 x H105mm ☞ Ø75mm
	112420	20W	SMD	54	85 lm/W	Ø105 x H112mm ☞ Ø95mm

Color Options	Reflector Options
☐ W ☐ B ☐ C ☒ G	☐ W ☐ B ☐ C ☒ G



2700K
3000K
4000K
5000K
6000K

DALI
1-10 Dimming
Phase Dimming