



Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Frosted glass diffuser, UV stabilized with a better light output.

Reflector - Pure anodized aluminium reflector, UV stabilized.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

This spotlight is one of the basic recessed spotlight range. It is design to give a warm and relaxing ambience. As for energy consumption this LED lights is surely saves and using less consumption due to its lighting capabilities. This is suitable for a wide variety of applications. Completely dustproof. Protected against splash of water.

Obbiettivo

Il faretto per far fuoco è uno dei faretti da incasso di base. È design per dare un ambiente caldo e rilassante. Per quanto riguarda il consumo di energia, questa luce a LED è sicuramente un risparmio e utilizza meno consumi grazie alle sue capacità di illuminazione. Questo è adatto per un'ampia varietà di applicazioni. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	1133010	10W	COB	44	95 lm/W	88 x 89mm Ø80mm
	1133110	10W	COB	44	95 lm/W	88 x 89mm Ø80mm

