



114400

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Clear tempered glass diffuser. UV stabilized with a better light output.

Reflector - LED lamp reflector. UV stabilized.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

The COB LED technology permits to maintain high lumen performance in the mini size. The customized colour option is a must, the application places are too many to be mentioned. The tested IP 65 is a plus to permit the application of the item even in difficult conditions, where the humidity percentage is high, or in exposed to the weather condition places. Completely dustproof.

Protected against jets of water.

Obbiettivo

La tecnologia LED COB consente di mantenere elevate prestazioni lumen nelle dimensioni mini. L'opzione di colore personalizzata è un must, I posti di applicazione sono troppi per essere menzionati. L'IP 65 testato è un vantaggio per consentire l'applicazione dell'articolo anche in condizioni difficili, dove la percentuale di umidità è elevata o esposta alle condizioni meteorologiche.

Completamente antipolvere. Protetto contro i getti d'acqua.

	CODE	POWER	BULB	IP	LUMEN	NS DIMEN	SION	
	114400	6W / 8W / 12W	MR16	65	95lm/\	N Ø86 x H9	9mm ጭ Ø70m	m
	© Ø70mm O Ø86 Color Options W S B	99	Beam A	angle 44°		550 11100 1650 2200	2700K 3000K 4000K 5000K 6000K	DALI 1-10 Dimming Phase Dimming
RoHS CE	w 👣 🎕	LED (1)	F	CRI >90	-20° C 55° C	85~265V E RIDON 50/60Hz	S BRIDGELUX	A++



