



115803



115903



116003

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - PMMA Lens diffuser, UV stabilized with a better light output.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

This good looking downlight guarantees satisfying results. Perfect for work lighting especially in places where a lot of nice and bright light is required. LED energy saving consumptions yet gives a great bright and calm ambience. Completely dustproof. Protected against splash of water.

Obbiettivo

Questo downlight dall'aspetto elegante garantisce risultati soddisfacenti. Perfetto per l'illuminazione di lavoro, specialmente in luoghi dove è richiesta molta luce piacevole e brillante. I consumi energetici a LED offrono ancora un ambiente luminoso e calmo. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	115803	3W	COB	44	70 lm/W	Ø49.6 x 28.4mm ☞ Ø42mm
	115903	3W	COB	44	70 lm/W	Ø41.5 x 30.6mm ☞ Ø35mm
	116003	3W	COB	44	70 lm/W	Ø41.7 x 30mm ☞ Ø35mm

