




1193206 / 12 / 18

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - PMMA diffuser, UV stabilized with a better light output.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).



Objective

This luminaire is a good choice in matter of design and power. This high efficiency of the LED source ensures excellent performances and low consumptions. Energy and economy savings are a little advantage compared to the design of this item. Completely dustproof. Protected against splash of water.


Obbiettivo

Questo apparecchio è una buona scelta in termini di design e potenza. Questa elevata efficienza della sorgente LED garantisce prestazioni eccellenti e bassi consumi. Risparmio energetico ed economico sono un piccolo vantaggio rispetto al design di questo prodotto. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.


	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	1193206	2*6W	COB	54	95 lm/W	142 x 72 x H62mm ☯ 130 x 60mm
	1193212	2*12W	COB	54	95 lm/W	173 x 88 x H71mm ☯ 160 x 75mm
	1192218	2*18W	COB	54	95 lm/W	210 x 102 x H86mm ☯ 195 x 90mm



Beam Angle



Color Options



2700K
3000K
4000K
5000K
6000K

DALI
1-10 Dimming
Phase Dimming

