



120510 / 18 / 25 / 30

Description

Housing - Die cast aluminium with powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Polycarbonate PMMA diffuser, UV stabilized with a better light output.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

High efficiency LED downlight. This fitting gives great functionality and efficiency. The design is consistent. The light provided from this luminaire is uniform and there is no glare effect. Expect LED energy saving consumption and durability. Completely dustproof. Protected against splash of water.

Obbiettivo

Downlight LED ad alta efficienza. Questo raccordo offre grande funzionalità ed efficienza. Il design è coerente. La luce fornita da questo apparecchio è uniforme e non vi è alcun effetto di abbagliamento. Aspettatevi consumi e durata a risparmio energetico a LED. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	120510	10W	SMD	65	95 lm/W	Ø115 x H48mm
	120518	18W	SMD	65	95 lm/W	Ø159 x H60mm
	120525	25W	SMD	65	95 lm/W	Ø190 x H60mm
	120530	30W	SMD	65	95 lm/W	Ø230 x H72mm

