



143307 / 13

Description

Material - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Polycarbonate diffuser, UV stabilized with a better light output.

Mounting - LED Surface wall mounted.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

This luminaire is characterized as one of the innovative in the LED technology. Through Innovation and research this luminaire becomes more efficient and durable. It gives pleasant and comfortable to ones eye. LED energy consumption savings.

Completely dustproof. Protected against jets of water.

Obbiettivo

Questo apparecchio è caratterizzato come uno degli innovativi nella tecnologia LED. Attraverso l'innovazione e la ricerca, questo apparecchio diventa più efficiente e durevole. Dà piacevole e confortevole per gli occhi. Risparmio sui consumi energetici a LED.

Completamente antipolvere. Protetto contro i getti d'acqua.



	CC	ODE POWER	R TYPE	IP	LUMENS	DIMENSION	
/ / / /							
	143	3307 7W	SMD	66	90 lm/W	162 x 90 x 96mm	
	143	3313 13W	SMD	66	90 lm/W	200 x 90 x 96mm	



















-20° C 85~265V 55° C 50/60Hz legg<u>ero</u>



2700K 3000K

4000K 5000K

6000K



