



140120

Description

Material - Die cast Aluminium with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Polycarbonate diffuser, UV stabilized.

Mounting - LED Surface ceiling mounted.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective


This surface luminaire with LED integral power supply unit have a unique design that gives classy, cool and warm ambience to the surroundings. This LED advance technology, together with the high quality materials ensures long life and LED energy savings consumptions. Completely dustproof. Protected against jets of water.

Obiettivo

Questo apparecchio di superficie con alimentatore integrato a LED ha un design unico che conferisce un ambiente elegante, caldo e accogliente all'ambiente circostante. Questa tecnologia avanzata a LED, insieme ai materiali di alta qualità, assicura una lunga durata e consumi energetici a LED. Completamente antipolvere. Protetto contro i getti d'acqua.




CODE	POWER	TYPE	IP	LUMENS	DIMENSION
 140120	20W	LED	65	90 lm/W	251 x 55 x 251mm



Color Options

SG DG B

Beam Angle



2700K
3000K
4000K
5000K
6000K



IK08

CRI >90

-20°C
55°C

85~265V
50/60Hz

leggero
PHILIPS

LED CHIPS
BRIDGELUX
CREE

