



140912

Objective

This luminaire is characterized as one of the innovative in the LED technology. Through Innovation and research this luminaire becomes more efficient and durable. It gives pleasant and comfortable to ones eye. LED energy consumption savings.

Completely dustproof.

Protected against jets of water.

Obbiettivo

Questo apparecchio è caratterizzato come uno degli innovativi nella tecnologia LED. Attraverso l'innovazione e la ricerca, questo apparecchio diventa più efficiente e durevole. Dà piacevole e confortevole per gli occhi. Risparmio sui consumi energetici a LED.

Completamente antipolvere.

Protetto contro i getti d'acqua.

Description

Material - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Polycarbonate diffuser, UV stabilized with a better light output.

Mounting - LED Surface wall mounted.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).




CODE	POWER	TYPE	IP	LUMENS	DIMENSION
140912	12W	SMD	65	90 lm/W	236 x 68 x 114mm



Color Options

SG DG ●

Beam Angle



2700K
3000K
4000K
5000K
6000K