



141212

Description

Material - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Polycarbonate diffuser.
UV stabilized with a better light output.

Mounting - LED Surface wall mounted.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability.
Efficiency and quality in wide variation.
50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective


This surface wall luminaire have a unique design that gives classy, cool and warm ambience to the surroundings. This LED advance technology, together with the high quality materials ensures long life and LED energy savings consumptions. Protected against the penetration by solid bodies. Protected against rain.

Obbiettivo

Questo apparecchio a parete di superficie ha un design unico che conferisce un ambiente elegante, caldo e accogliente all'ambiente circostante. Questa tecnologia avanzata a LED, insieme ai materiali di alta qualità, assicura una lunga durata e consumi energetici a LED. Protetto contro la penetrazione di corpi solidi. Protetto contro gli spruzzi d'acqua.




CODE	POWER	TYPE	IP	LUMENS	DIMENSION
141212	12W	SMD	65	90 lm/W	198mm x 77mm x 131mm



Color Options

S DG B



2700K
3000K
4000K
5000K
6000K



IK08

CRI >90

-20° C
55° C

85~265V
50/60Hz

Leggero
PHILIPS

LED Chips
BRIDGELUX
CREE

