

143611

Description

Material - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Polycarbonate diffuser, UV stabilized with a better light output.

Mounting - LED Surface wall mounted.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

This luminaire is characterized as one of the innovative in the LED technology. Through Innovation and research this luminaire becomes more efficient and durable. It gives pleasant and comfortable to ones eye. LED energy consumption savings.

Protected against the penetration by solid bodies. Protected against rain.

Obbiettivo


Questo apparecchio è caratterizzato come uno degli innovativi nella tecnologia LED. Attraverso l'innovazione e la ricerca, questo apparecchio diventa più efficiente e durevole. Dà piacevole e confortevole per gli occhi. Risparmio sui consumi energetici a LED.

Protetto contro la penetrazione di corpi solidi. Protetto contro gli spruzzi d'acqua.



CODE	POWER	BULB	IP	LUMENS	DIMENSION
------	-------	------	----	--------	-----------



143611	11W	SMD	65	90 lm/W	106 x 62 x 200mm
--------	-----	-----	----	---------	------------------



Color Options

SG DG B

Beam Angle



2700K
3000K
4000K
5000K
6000K



IK09

CRI >90

-20° C 55° C

85~265V 50/60Hz

leggero
PHILIPS

BRIDGELUX
LED Chips
CREE

