



145411 / 15 / 22 / 30

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Reflector - Anodized aluminium reflector, UV stabilized.

Mounting - LED Surface wall mounted.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).


Objective

This luminaire's unique design gives a pleasant and warm ambience to one's eye. Due to LED characteristics this fitting gives more efficiency and durability on itself. LED energy saving consumption is expected. Durability and long lasting quality is expected. Completely dustproof. Protected against jets of water.



Obiettivo

Questo design unico di apparecchi di illuminazione offre un ambiente piacevole e caldo alla vista. Grazie alle caratteristiche del LED, questo apparecchio offre maggiore efficienza e durata su se stesso. Si prevede un consumo di risparmio energetico a LED. Sono previste resistenza e qualità duratura. Completamente antipolvere. Protetto contro i getti d'acqua.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	145411	1*11W	COB	66	100 lm/W	Ø110 x 130mm
	145415	1*15W	COB	66	100 lm/W	Ø110 x 130mm
	145422	2*11W	COB	66	100 lm/W	Ø110 x 200mm
	145430	2*15W	COB	66	100 lm/W	Ø110 x 200mm



Color Options



2700K
3000K
4000K
5000K
6000K

