

1458105



1458205

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Reflector - Aluminium reflector, UV stabilized.

Mounting - LED Surface wall mounted.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

Energy efficient light that gives convenient lighting effect to the environment. Luminous effect of the light gives a warm and calming effect to the surroundings. Energy saving consumption is assured. Completely dustproof. Protected against jets of water.

Obbiettivo

Luce ad alta efficienza energetica che offre un pratico effetto luminoso all'ambiente. L'effetto luminoso della luce dona un effetto caldo e rilassante all'ambiente circostante. Il risparmio energetico è assicurato. Completamente antipolvere. Protetto contro i getti d'acqua.

CODE

POWER

CHIP

IP

LUMENS

DIMENSION



1458105

1*5W

COB

65

100 lm/W

68 x 92 x 81mm



1458205

2*5W

COB

65

100 lm/W

68 x 92 x 150mm





Color Options

S

B

Beam Angle



2700K

3000K

4000K

5000K

