



1706112 / 15 / 20

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Reflector - Aluminium reflector, UV stabilized.

Mounting - LED Surface mounted.

Standards - Manufactured and tested as per EN 60598-1 and 60598-2-1.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

Providing a projector like light is the primary characteristics of this tracklight. As this is an LED based light it will surely produces high quality and efficient performance light. Works perfectly in accordance of LED energy savings. Durability and efficiency is expected on this luminaire. Protected against the penetration by solid bodies. Protected against sprays of water.

Obiettivo

Fornire un proiettore come la luce è la caratteristica principale di questo proiettore. Poiché si tratta di una luce a LED, produrrà sicuramente luce ad alte prestazioni ed efficienza. Works perfectly in accordance of LED energy saving. La durabilità e l'efficienza sono attese su questo apparecchio. Protetto contro la penetrazione di corpi solidi. Protetto contro gli spruzzi d'acqua.

CODE	POWER	CHIP	IP	LUMENS	DIMENSION
------	-------	------	----	--------	-----------

 1706112	12W	COB	44	100 lm/W	Ø48 x 120mm
 1706115	15W	COB	44	100 lm/W	Ø58 x 135mm
 1706120	20W	COB	44	100 lm/W	Ø58 x 150mm





Color Options

W

B

G

Beam Angle



2700K

3000K

4000K

5000K

6000K

DALI

1-10 Dimming

Phase Dimming