



181600

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Reflector - Aluminium reflector, UV stabilized.

Mounting - LED Ceiling Surface mounted.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective


This cylindrical luminaire is very elegant yet Eco friendly surface downlight that will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption. Completely dustproof. Protected against splash of water.

Obbiettivo

Questo apparecchio cilindrico è un downlight di superficie molto elegante ma eco-friendly che ti garantirà che questo prodotto è durevole e durerà a lungo.. Dal momento che questa è una luce a LED, questo sicuramente ti farà risparmiare da un costoso consumo di energia. Si prevede di fornire ottimi risultati con un consumo minimo. Completamente antipolvere. Protetto contro gli spruzzi d'acqua.

CODE	POWER	BULBS	IP	LUMENS	DIMENSION
------	-------	-------	----	--------	-----------


 181600	6W / 8W / 12W	MR16	65	100 lm/W	Ø90 x 130mm
--	---------------	------	----	----------	-------------



Color Options

(W) (B)

Beam Angle



2700K

3000K

4000K

5000K

6000K

DALI

1-10 Dimming

Phase Dimming