



of colors, radiation protection, UV with high mechanical resistance.

Diffuser - Acrylic diffuser, UV stabilized with a better light output.

Mounting - LED Surface / Pendant mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

Eco friendly surface downlight yet will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption.

Completely dustproof.

Protected against high pressure water jets.

Obbiettivo

Il downlight di superficie eco-compatibile ti garantirà comunque che questo prodotto è durevole e durerà a lungo. Dal momento che questa è una luce a LED, questo sicuramente ti farà risparmiare da un costoso consumo di energia. Si prevede di fornire ottimi risultati con un consumo minimo.

Completamente antipolvere.

Protetto contro i getti d'acqua ad alta pressione.



CODE	POWER	CHIP	IP	LUMENS	DIMENSION	
1843020	20W	SMD	40	80 lm/W	Ø400 x H87 mm	
1843030	30W	SMD	40	80 lm/W	Ø400 x H87 mm	
1843040	40W	SMD	40	80 lm/W	Ø600 x H87 mm	
1843050	50W	SMD	40	80 lm/W	Ø600 x H87 mm	
1843070	70W	SMD	40	80 lm/W	Ø1200 x H87 mm	
1843100	100W	SMD	40	80 lm/W	Ø1200 x H87 mm	

