

Description

CODE

High quality chip and weatherproof LED. Double souldering, Excellent performance and energy savings. Completely dustproof. Radiation protection, UV with high mechanical resistance. LED energy consumption savings with durability and luminaire with efficiency.

Mounting - LED Surface/Recessed mounted.

Standards - Manufactured and tested as per EN 60598-1 and 60598-2-1

CHIP

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

POWER

Objective

This High quality flexible SMD LED striplight with high effiency and guaranteed to give excellent results and surely give a unique lighting effect and pleasantly light. Excellent performance and energy savings. Environmental friendly thanks to the energy and consumption savings guaranteed from its characteristics. Completely dustproof.

Protected from temporary immersion.

Obbiettivo

Questo Striplight LED SMD flessibile di alta qualità con alta efficienza e garantito per dare risultati eccellenti e sicuramente dare un effetto di illuminazione unico e piacevolmente leggero. Prestazioni eccellenti e risparmio energetico. Rispetto dell'ambiente grazie al risparmio di energia e di consumo garantito dalle sue caratteristiche.

LED TYPE

PCB WIDTH

LED

Completamente antipolvere.

LUMENS

Protetto dall'immersione temporanea.

	1	190704	4.8W	SMD	20/65/67	90 lm/W 11	10 lm/W	5050	10mm	120 / m
	1	190709	9.6W	SMD	20/65/67	90 lm/W 11	10 lm/W	5050	10mm	120 / m
	1	190714	14.4W	SMD	20/65/67	90 lm/W 11	10 lm/W	5050	10mm	120 / m
	F-1	-	m/196.9±1.4° 西/2 □•□•□•□ 町 □ □•□ 36mm/196.9±1.4°	12±0.2m			-	±180	150	RGB
50±0.5mm/ 50±0.000									120	2700K 3000K DALI 4000K 1-10 Dimming
	*	8.3±0.5mm/0.33	1840 84 84 84 84 84 84 84 84 84 84 84 84 84	79 79 79 79	Color Options w	120°	-60	200 250 300		5000K Phase Dimming 6000K
RoHS	E U/	Ç)		(I)	F	CRI >90	-20° C 55° C	03~203V §	TOICSAUC U	DGELUX.

IΡ