



2726006 / 12 / 24 / 36 / 50

**Description**

**Housing** - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

**Diffuser** - Tempered glass diffuser, UV stabilized with a better light output.

**Type** - LED Recessed mounted.

**Standards** - Manufactured and tested as per EN 60598-1 and 60598-2-1.

**LED** - Energy saving consumption and Durability. Efficiency and quality in wide variation. 60,000 Hrs Life span under temperature (-20°C to 55°C).

**Objective**

Eco friendly recessed light fittings yet will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption.

Completely dustproof. Protected from temporary immersion.

**Obiettivo**

Gli apparecchi di illuminazione da incasso vi garantirà tuttavia che questo prodotto è durevole e durerà a lungo. Dato che si tratta di una luce a LED, questo ti farà sicuramente risparmiare da un costoso consumo di energia. Previsto per fornire I grandi risultati sul consumo minimo.

Completamente antipolvere. Prote o dall'immersione temporanea.

CODE	POWER	CHIP	IP	LUMENS	DIMENSION (Ø x H x B)
2726006	6W	SMD	67	660 lm	Ø100 x 120 x Ø65mm
2726012	12W	SMD	67	1320 lm	Ø160 x 155 x Ø120mm
2726024	24W	SMD	67	2640 lm	Ø210 x 160 x Ø160mm
2726036	36W	SMD	67	3960 lm	Ø260 x 155 x Ø200mm
2726054	54W	SMD	67	5940 lm	Ø260 x 155 x Ø200mm

