



## **Description**

**Housing** - Stainless Steel frame with extruded Aluminium body material, radiation protection, UV with high mechanical resistance.

**Diffuser** - Tempered glass diffuser, UV stabilized with a better light output.

Type - LED Recessed mounted.

**Standards** - Manufactured and tested as per EN 60598-1 and 60598-2-1.

**LED** - Energy saving consumption and Durability. Efficiency and quality in wide variation. 60,000 Hrs Life span under temperature (-20°C to 55°C).

## **Objective**

Eco friendly recessed light fittings yet will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption.

Completely dustproof.

Protected from temporary immersion.

## <u>Obbiettivo</u>

Gli apparecchi di illuminazione da incasso vi garantirà tuttavia che questo prodotto è durevole e durerà a lungo. Dato che si tratta di una luce a LED, questo ti farà sicuramente risparmiare da un costoso consumo di energia. Previsto per fornire I grandi risultati sul consumo minimo.

□ CREE €

Completamente antipolvere.

Prote o dall'immersione temporanea.

50/60Hz

		CODE	POWER	CHIP	IP	LUMENS	DIMENSION ( L x W x F	H )
	1	2733012	12W	SMD	67	100 lm/W	1000 x 21 x 45mm	
	1	2733015	15W	SMD	67	100 lm/W	1000 x 21 x 45mm	
	Color Op	_	67 45 58 90 62 78	Beam An  8°  105 25°  45°   15*45°	15°	-150 ±180 -150 -150 -120 -60 -30 1166	RGB 2700K 3000K 4000K 5000K	RDM  DALI  0-10 Dimning  DMX
1 (6)				<b>F</b> /   K10	<u></u> CRI	-20° C 85~26	Leggero* PHILIPS TRIDONIC BRIDGELUX	<b>A++</b>