

2742022

Description

Housing - Stainless Steel cover & Aluminium material, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Type - LED Recessed mounted.

Standards - Manufactured and tested as per EN 60598-1 and 60598-2-1.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 60,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

Eco friendly recessed light fittings yet will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption.

Completely dustproof.

Protected from temporary immersion.

<u>Obbiettivo</u>

Gli apparecchi di illuminazione da incasso vi garantirà tuttavia che questo prodotto è durevole e durerà a lungo. Dato che si tratta di una luce a LED, questo ti farà sicuramente risparmiare da un costoso consumo di energia. Previsto per fornire I grandi risultati sul consumo minimo.

Completamente antipolvere.

Prote o dall'immersione temporanea.

		CODE	POWER	CHIP	IP	LUMENS	DIMENSIO	N (Ø x H x	B)
1 1	1	2742022	22W	SMD	67	100 lm/W	Ø210 x 12	0 x Ø185m	m
	C	olor Options	Ø210 Ø145.5 Ø185	20°		-150 -150 -150 -100	150 120 90 60	RGB 2700K 3000K 4000K 5000K	RDM DALI 1-10 Dimming DMX





















-20° C **DC 12V** 50/60Hz 55° C

PHILIPS TRIDONIC

BRIDGELUX CREE

