



2742214-B / 32

Description

Housing - Stainless Steel cover & Aluminium material, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Type - LED Recessed mounted.

Standards - Manufactured and tested as per EN 60598-1 and 60598-2-1.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 60,000 Hrs Life span under temperature (-20°C to 55°C).

Objective


Eco friendly recessed light fittings yet will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption.

Completely dustproof.
Protected from temporary immersion.



Obbiettivo

Gli apparecchi di illuminazione da incasso vi garantirà tuttavia che questo prodotto è durevole e durerà a lungo. Dato che si tratta di una luce a LED, questo ti farà sicuramente risparmiare da un costoso consumo di energia. Previsto per fornire i grandi risultati sul consumo minimo. Completamente antipolvere. Prote o dall'immersione temporanea.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION (Ø x H x B)
	2742214-B	14W	SMD	67	100 lm/W	Ø250 x 196 x Ø235mm
	2742232	32W	SMD	67	100 lm/W	Ø250 x 196 x Ø235mm



Beam Angle



Floor recessed

