



284015

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Reflector - Optical Lens, UV stabilized.

Type - LED Outdoor.

Standards - Manufactured and tested as per PTPS IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).


Objective

This have a unique design and will be fitted everywhere in external areas. This is very suitable in private gardens, public parks and etc. This light delivers excellent performance and outstanding fitting durability. Completely dustproof. Protected against high pressure water jets.

Obiettivo

Questa luce offre prestazioni eccellenti e una straordinaria durata nel montaggio. Questo è molto adatto in giardini privati, parchi pubblici ed ecc. Inoltre, questo ha un design unico e verrà montato ovunque nelle aree esterne. Completamente antipolvere. Protetto contro i getti d'acqua ad alta pressione.



CODE	POWER	TYPE	IP	LUMENS	DIMENSION
284015	15W	SMD	65	90 lm/W	180 x 80 x 900mm



Color Options

S B

Beam Angle



2700K
3000K
4000K
5000K
6000K



CRI >90

-20°C
55°C

85~265V
50/60Hz

leggero
PHILIPS

LED Chips
BRIDGELUX
CREE

