



287215 / 25

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Reflector - Aluminium reflector, UV stabilized.

Type - LED Outdoor.

Standards - Manufactured and tested as per PTSP IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective


This light delivers excellent performance and outstanding fitting durability. This is very suitable in private gardens, public parks and etc. Also, this have a unique design and will be fitted everywhere in external areas. Completely dustproof. Protected against high pressure water jets.

Obbiettivo

Questa luce offre prestazioni eccellenti e una straordinaria durata nel montaggio. Questo è molto adatto in giardini privati, parchi pubblici ed ecc. Inoltre, questo ha un design unico e verrà montato ovunque nelle aree esterne. Completamente antipolvere. Protetto contro i getti d'acqua ad alta pressione.





CODE	POWER	TYPE	IP	LUMENS	DIMENSION
287215	15W	SMD	65	90 lm/W	Ø160 x 1000mm
287225	25W	SMD	65	90 lm/W	Ø160 x 1000mm



Color Options

G B

Beam Angle



2700K
3000K
4000K
5000K
6000K