



124512 / 15 / 25 / 36 / 45

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

This downlight has a wide choice of wattage. High quality and efficiency fitting made. LED energy saving consumption and high resistance and last long. Due to Innovation and research this downlight is made of advance technologies and guarantees very calm and bright lighting to the environment. Completely dustproof. Protected against jets of water.

Obbiettivo

Questo faretto ha una vasta scelta di potenza. Realizzazione di alta qualità ed efficienza. Risparmio energetico a LED, alta resistenza e lunga durata. Grazie all'innovazione e alla ricerca, questo downlight è realizzato con tecnologie avanzate e garantisce un'illuminazione molto calma e luminosa all'ambiente. Completamente antipolvere. Prote o contro getti d'acqua.

	CODE	POWER		IP	LUMENS	DIMENSION
	124512	12W	COB	65	95 lm/W	Ø86 x 54mm ☛ Ø75mm
	124515	15W	COB	65	95 lm/W	Ø100 x 64mm ☛ Ø90mm
	124525	25W	COB	65	95 lm/W	Ø136 x 83mm ☛ Ø125mm
	124536	36W	COB	65	95 lm/W	Ø158 x 96mm ☛ Ø145mm
	124545	45W	COB	65	95 lm/W	Ø190 x 109mm ☛ Ø165mm

