



124612 / 15 / 25 / 36

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Mounting - LED Recessed mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

This downlight has a wide choice of wattage. High quality and efficiency fitting made. LED energy saving consumption and high resistance and last long. Due to Innovation and research this downlight is made of advance technologies and guarantees very calm and bright lighting to the environment. Completely dustproof. Protected against jets of water.

Obbiettivo

Questo faretto ha una vasta scelta di potenza. Realizzazione di alta qualità ed efficienza. Risparmio energetico a LED, alta resistenza e lunga durata. Grazie all'innovazione e alla ricerca, questo downlight è realizzato con tecnologie avanzate e garantisce un'illuminazione molto calma e luminosa all'ambiente. Completamente antipolvere. Prote o contro getti d'acqua.



	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	124612	12W	COB	65	95 lm/W	110 x 110 x 64mm ☞ 90 x 90mm
	124615	15W	COB	65	95 lm/W	136 x 136 x 83mm ☞ 125 x 125mm
	124625	25W	COB	65	95 lm/W	158 x 158 x 96mm ☞ 145 x 145mm
	124636	36W	COB	65	95 lm/W	180 x 180 x 109mm ☞ 160 x 160mm



Color Options



Beam Angle



2700K
3000K
4000K
5000K
6000K

