



187115 / 20 / 30 / 40 / 50

Description

Housing - Die cast aluminium powder coated with choice of RAL colors, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered glass diffuser, UV stabilized with a better light output.

Reflector - PMMA reflector, UV stabilized.

Mounting - LED Ceiling Surface mounted.

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 55°C).

Objective

Perfect for work lighting especially in places where a lot of nice and bright light is required. Since downlight has the advantage of light adjustment they can be installed around the edge of the room to get that clean and streamlined light for that perfect ambience. Protected against the penetration by solid bodies. Protected against jets of water.

Obbiettivo

Perfetto per l'illuminazione di lavoro soprattutto in luoghi dove molto bello e luminoso è richiesta luce. Dal momento che il downlight ha il vantaggio della regolazione della luce loro può essere installato facilmente lungo il bordo del spazio per ottenere quello pulito e aerodinamico luce per l'atmosfera perfetta. Protetto contro la penetrazione di corpi solidi. Protetto contro i getti d'acqua.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
	187115	15W	COB	65	100 lm/W	Ø80 x H90mm
	187120	20W	COB	65	100 lm/W	Ø100 x H100mm
	187130	30W	COB	65	100 lm/W	Ø130 x H130mm
	187140	40W	COB	65	100 lm/W	Ø150 x H140mm
	187150	50W	COB	65	100 lm/W	Ø170 x H160mm

