

273818 / 24 / 36

Description

Housing - Made of good quality 304 stainless steel cover with 6063 extuded aluminum alloy lamp body, radiation protection, UV with high mechanical resistance.

Diffuser - Tempered diffuser, UV stabilized with a better light output.

Mounting - LED recessed luminaire

Standards - Manufactured in accordance with IEC 62722.

LED - Energy saving consumption and Durability. Efficiency and quality in wide variation. 50,000 Hrs Life span under temperature (-20°C to 60°C).

Objective

Eco friendly recessed luminaire yet will guaranteed you that this product is durable and will last long. Since this is LED light this will surely saves you from a costly consumption of energy. Expected to provide the great results on minimal consumption.

Completely dustproof.

Protected from temporary immersion.


Obbiettivo

L'apparecchio d'illuminazione di Incasso ecologica vi garantirà tuttavia che questo prodotto è durevole e durerà a lungo. Dato che si tratta di una luce a LED, questo ti farà sicuramente risparmiare da un costoso consumo di energia. Previsto per fornire I grandi risultati sul consumo minimo.

Completamente antipolvere.

Protetto dall'immersione temporanea.

	CODE	POWER	CHIP	IP	LUMENS	DIMENSION
1	273818	18W	SMD	67	100 lm/W	1000 x 75 x 84mm
1	273824	24W	SMD	67	100 lm/W	1000 x 75 x 84mm
1	273836	36W	SMD	67	100 lm/W	1000 x 75 x 84mm
			D.	oom Anglo		
			Beam Angle		±180	























-20° C 60° C AC100V-265V DC24V 50/60Hz

Leggéro° PHILIPS TRIDONIC

BRIDGELUX GREE €



Floor recessed